

Technical Data Sheet redstone™ - WOS PRIMER

Special primer for moisture absorbing surfaces

Area of application:

redstone™ WOS Primer:

- for the solidification and regulation of absorptive capacity of surfaces

Properties:

redstone™ WOS Primer

- high solidification
- allows vapor diffusion
- odorless
- regulation of absorptive capacity by crystallization
- highly alkaline

Technical data:

Material	water dispersed primer
Specific weight	approx. 1.05 kg/dm ³
pH value	approx. 8 - 8.5
Usage	0.5 to 1.0 fl oz/ ft ² (150 to 300 ml/ m ²)

Directions for use:

Pre-treatment of surface:

Surfaces must be free of residuals (acid salts, bitumen, coatings, oil and the like). Protect window sills, mounted parts, glass, ceramic, clinker, natural stone, coated and anodized surfaces from penetration by masking.

Processing:

Apply redstone™ WOS Primer approx. 0.45 - 0.9 oz per ft² undiluted by spraying, brushing or with a paint roller.

Processing temperature:

The surface and ambient temperatures should not drop under +8°C.

The data contained in this document are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions or technical data etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. All former technical leaflets are replaced by this one.

Drying time:

Approx. 30 minutes depending on temperature and humidity.

Cleaning:

Clean tools with water immediately after use.

Content:

1.05 qt./ 33.8 fl oz (1 ltr) bucket

10.5 qt./ 338 fl oz (10 ltr) bucket

Safety Advices:

Caution:

- May cause irritation to eyes and skin
- Dust may irritate the respiratory system
- Keep out of reach of children
- Avoid skin contact
- Avoid contact with eyes
- Avoid prolonged inhalation of fumes
- Do not ingest

First Aid:

- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice if symptoms occur
- In case of contact with skin, wash immediately with soap and water and seek medical advice if irritation develops
- If swallowed, contact physician immediately for assistance

Storage:

Close container air-tight and store in a cool (frost-free), dry and well ventilated location. Storage shelf life in original packaging: 6 months.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

Material Safety Data Sheet:

MSDS provided upon request.

The data contained in this document are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions or technical data etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed. All former technical leaflets are replaced by this one.